



## Rostfreier Blankstahl, Rund

### Rundstahl +C gezogene oder +SH geschälte Stäbe

EN 10088-3/2014, Toleranz h9/h11 Ausführung richtpoliert oder geschliffen EN 10278

in Längen von 3000 mm - 0/+ 200 mm

Güte/ Abm. mm	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0	14.0	15.0	16.0
1.4021+QT				o	o	+		+		+		+		+	+	+
1.4034+A						+		o		+		+		o	o	+
1.4057+QT						+		+		+		+		+	+	+
1.4104+A	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
1.4104+QT								+				+	+	o		+
1.4112+A					o	+		+		+			+	o	+	+
1.4122+QT										o		+	+	o	o	+
1.4301 +AT	+		+	+	+	+	+	+	+	+	o	+	+	+	+	+
1.4305	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
1.4404 +AT			o	o	+	+	o	+		+			o	+	+	+
1.4571 +AT	o		+	+	+	+	o	+	+	+	o	+	o	+	+	+

Güte/Abm. mm	17.0	18.0	19.0	20.0	22.0	23.0	24.0	25.0	26.0	27.0	28.0	30.0	32.0	35.0	36.0	38.0
1.4021+QT	o	+		+	+		+	+	+		+	+	+	+	+	
1.4034+A		o		o	o			o				o		o		
1.4057+QT		+		+	+		+	+	+	o		+	o	+		
1.4104+A	+	+	+	+	+	+	+	+	+	+	+	+	+	+	o	+
1.4104+QT		+		+	+			+	+		+	+	o	o		
1.4112+A		+		+	o			+	o			+		+		
1.4122+QT		+		+	+		+	o			o	+	o	o	o	o
1.4301 +AT	+	+	o	+	+		+	+	+		+	+	+	+	+	o
1.4305	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
1.4404 +AT	o	+		+	+		+	+	o		+	+	+	+	+	+
1.4571 +AT	+	+		+	+		+	+	o		+	+	+	+	+	o

Güte/Abm. mm	40.0	42.0	45.0	50.0	55.0	60.0	65.0	70.0	75.0	80.0	85.0	90.0	95.0	100	110	120
1.4021+QT	+		+	+	+	+	+	o		o						
1.4034+A	+		o	o				+								
1.4057+QT	+		+	+	+	o	+	o	+	+						
1.4104+A	+	+	+	+	+	+	+	+	o	+	+	+		+	+	+
1.4104+QT	o		o	o	o	+	o	o	o	o						
1.4112+A	+	+	o	+												
1.4122+QT	o	+	+	o												
1.4301 +AT	+	+	+	+	+	+	+	+	+	+	+	+	o	o		
1.4305	+	+	+	+	+	+	+	+	+	+	o	+	o	+		
1.4404 +AT	+	+	+	+	+	+	+	+		+		o				
1.4571 +AT	+	+	+	+	o	+	+	+	+	o		+		o		

+ aus Lagervorrat o aus freibleibendem Werksvorrat # weitere Abmessungen und Güten auf Anfrage!