



Werkzeugstahl

Silberstahl 1.2210 115CrV3, +A gegläht,

Rundstahl +C gezogene oder +SH geschälte Stäbe

Ausführung: gezogen, poliert ab dm. 3 mm geschliffen, poliert Toleranz h9/ EN 10278
in Längen von 2000 mm

| mm | *,0 | *,1 | *,2 | *,3 | *,4 | *,5 | *,6 | *,7 | *,8 | *,9 |
|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 1 | + | | o | o | | o | | | + | |
| 2 | + | o | o | o | | + | | | o | |
| 3 | + | + | + | o | | o | + | + | o | + |
| 4 | + | | + | + | + | + | | + | + | |
| 5 | + | + | + | + | + | + | + | + | o | |
| 6 | + | o | + | + | + | + | | o | + | + |
| 7 | + | + | + | + | | o | | o | + | + |
| 8 | + | o | o | o | | + | | o | | |
| 9 | + | | + | o | + | o | | o | + | + |
| 10 | + | o | + | o | | + | + | o | | |
| 11 | + | | o | o | | + | | | | |
| 12 | + | + | + | + | | + | | | o | |
| 13 | + | | + | o | | + | | | o | |
| 14 | + | | o | o | | o | | | o | |
| 15 | + | o | + | o | | o | | | o | |
| 16 | + | o | o | o | | o | | o | o | |
| 17 | + | | o | o | | o | | | o | |
| 18 | + | o | o | o | | o | | | | |
| 19 | + | | o | o | | + | | | o | |
| 20 | + | o | | | | + | | | | |
| 21 | o | | | | | o | | | | |
| 22 | + | | | o | | o | | | | |
| 23 | o | | | | | | | | | |
| 24 | + | | o | | | o | | | | |
| 25 | + | | + | | | o | | | o | |
| 26 | o | | | | | | | | | |
| 27 | o | | | | | | | | | |
| 28 | + | | o | | | o | | | | |
| 29 | o | | | | | | | | | |
| 30 | + | | o | o | | o | | | | |
| 35 | + | | | | | o | | | | |
| 40 | + | | | | | o | | | | |
| 45 | o | | | | | | | | | |
| 50 | + | | | | | | | | | |

+ aus Lagervorrat o aus freibleibendem Werksvorrat # weitere Abmessungen und Güten auf Anfrage!