



Blankstahl

Rundstahl +C gezogene oder +SH geschälte Stäbe

EN 10277/ 2018 Toleranz h11/h9 in Längen von 3000 oder 6000 mm - 0/+ 500 mm

Güte/ Abmessung mm	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0	14.0	15.0
ESP65 (16MnCr5+Pb)							o		+		o		o	o
16MnCr(S)5							+	o	+		+		+	+
42CrMo(S)4+QT					o		+		+	+	+		+	+
100Cr6+AC							+		+		+	+	+	

Güte/ Abmessung mm	16.0	17.0	18.0	19.0	20.0	21.0	22.0	23.0	24.0	25.0	26.0	27.0	28.0	30.0
ESP65 (16MnCr5+Pb)	+		o		o		+				o			+
16MnCr(S)5	+		+		+		+		o	+	+		+	+
42CrMo(S)4+QT	+		+		+		+		+	+	+		+	+
100Cr6+AC	+		+		+		+			+			+	+

Güte/ Abmessung mm	32.0	34.0	35.0	36.0	38.0	40.0	42.0	43.0	45.0	46.0	48.0	50.0	52.0	55.0
ESP65 (16MnCr5+Pb)	o		o	o		o	+		+			o		o
16MnCr(S)5	+		+	+	o	+	+		+		+	+		o
42CrMo(S)4+QT	+		+	+	+	+	+		+		o	+		+
100Cr6+AC	+		+			+			+			+		+

Güte/ Abmessung mm	58.0	60.0	62.0	65.0	70.0	72.0	75.0	80.0	85.0	90.0	95.0	100	105	110
ESP65 (16MnCr5+Pb)				+										
16MnCr(S)5	+	+		+	o		o	o		o		o		
42CrMo(S)4+QT	+	+		+	+		o	+		+		o		o
100Cr6+AC		o												

Güte/ Abmessung mm	115	120	130	140	150	160
ESP65 (16MnCr5+Pb)						
16MnCr(S)5						
42CrMo(S)4+QT		o			o	
100Cr6+AC						

+ aus Lagervorrat o aus freibleibendem Werksvorrat # weitere Abmessungen und Güten auf Anfrage!

